## Simple/Reliable/Green/Efficient



# **AIR INLETS**

Inlet window can adjust the area of air intake, control the wind speed and ventilation volume of the house, to achieve the ideal ventilation effect.



WEBSITE





### **Air Inlet With Spring**

- Driven to open, closed by spring tension.
- Rib-and-groove design for a tight seal when closed.

• Equipped with a guide plate to adjust the angle, ensuring airflow toward the center of the poultry house.

Category	parameters	
The material	PS	
The hole size	560mm (W) *270mm (H)	840mm(W)*270mm(H)
Area	0.11m²	0.16m²

### Air Inlet With Curved Door

- Driven to close under traction, opens by its own weight.
- Fitted with a PU seal for superior closing tightness.
- Adjustable guide plate for airflow direction.



Category	parameters	
The material	PP+PVC	
The hole size	800mm(W)*270mm(H)	1200mm(W)*270mm(H)
Area	0.16m²	0.24m²
N0. of pull arms	1	2

#### Side Wall Large Window System

- Driven to close, opens under its own weight.
- Rubber sealing strip ensures tight closing.
- Adjustable guide plate angles airflow toward the house center.

Category	parameters
The material	ABS+PVC
The hole size	800mm(W)*500mm(H)
Area	0.26m²
N0. of pull arms	1



### QINGDAO BIG HERDSMAN MACHINERY CO., LTD

Add: Yuehe road, Konggang industrial park, Qingdao city, Shandong Province, PR China Tel: +86-532-8493 3988 Website: www.bigherdsman.com



